(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 3 February 2005 (03.02.2005)

PCT

(10) International Publication Number WO 2005/010998 A1

(51) International Patent Classification7: 43/00, 29/00

H01L 29/82,

(21) International Application Number:

PCT/US2003/019772

(22) International Filing Date: 24 June 2003 (24.06.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(71) Applicant (for all designated States except US): INTER-NATIONAL BUSINESS MACHINES CORPORA-TION [US/US]; New Orchard Road, Armonk, NY 10504 (US).

(72) Inventor; and

- (75) Inventor/Applicant (for US only): GAIDIS, Michael, C. [US/US]; 5 Hiview Road, Wappingers Falls, NY 12590 (US).
- (74) Agent: PEPPER, Margaret, A.; International Business Machines Corporation, 2070 Route 53, Hopewell Junction, NY 12533 (US).

- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, IP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report
- with a declaration as to non-prejudicial disclosures or exceptions to lack of novelty

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SELF-ALIGNED CONDUCTIVE LINES FOR FET-BASED MAGNETIC RANDOM ACCESS MEMORY DEVICES AND METHOD OF FORMING THE SAME

(57) Abstract: A conductive line structure for a field effect transistor (FET) based magnetic random access memory (MRAM) device includes a lateral metal strap (326) conductively coupled to a lower metallization line (302). A magnetic tunnel junction (MTJ) stack (316) is formed on the metal strap (326), and a metal shield (324) is formed over the MTJ stack (316), the metal shield (324) being self-aligned with respect to the metal strap (326). An upper metallization line (332) is conductively coupled to the metal shield (324), wherein the metal shield (324) serves as an etch stop during the formation of the upper metallization line (332).

